sewoo

DIRECT THERMAL POS PRINTER

SLK-TL212II



- Energy star qualified for power efficiency
- High speed printing : 220mm/sec
- Paper width adjustable 50~82.5mm
- ESC/POS command compatible
- Wall mount installation availadle

Barcode

Durable

Paper Width

Paper Sensor

Easy Loading

Fast Speed

Compact Design

Easy Maintenance

Energy Star

APPLICATION



SPECIFICATIONS

PRINTER CHARACTERISTICS

Print Method
Direct thermal
Print Speed
Up to 8.6ips(220mm/sec)
Print Width
Up to 2.8"(72mm)
Resolution
180dpi
Power
Power type : External SMPS
AC : 100~240Vac 50/60Hz
DC : 24Vdc / 1.75A
Sensor
Standard: Paper End, Paper Low, Cover Open
Option : Black Mark
Reliability
TPH life : 160km
MCBF : 60 Million lines
Cutter life : 1.8 Million cuts
Drawer port
2 circuits(24V, 1A Max.)

PHYSICAL CHARACTERISTICS

Dimension (W x D x H)
5.98" x 8.03" x 5.82"
(152 x 204 x 150mm)
Weight
3.74lb(1.7Kg)

INTERFACES

Standard
USB(B type)+ Serial (RS-232C_9pin) Built-in

CERTIFICATIONS

CE, FCC, KC, UL/cUL, ENERGY STAR

OPERATING CHARACTERISTICS

Operating Temperature
32 ~ 113°F(0 ~ 45°C)
Operating Humidity
10 ~ 80RH%
Storage Temperature
-4 ~ 140°F(-20 ~ 60°C)
Storage Humidity
10 ~ 90%

MEDIA CHARACTERISTICS

Media Type
Thermal recipt paper, Linerless(Optional)
Media Width
1.9~3.2"(50mm ~82.5mm)
Media Core Diameter
0.4"(12.5mm ± 0.5mm)
Media Roll Diameter
3.1"(ø 80mm)
Thickness
0.06~0.09mm

SOFTWARE

Emulations
ESC/POS Command compatible
Drivers
Windows Driver(XP ~, Server2003 ~), Windows CE & Mobile Driver (CE 4.2 ~, Mobile 5.0 ~), Linux Driver, Mac Driver, OPOS Driver, JavaPOS Driver, iOS SDK, Android(6.0 ~) SDK, Windows SDK, Windows CE SDK Linux SDK

BARCODES

1D
EAN-8, EAN-13, Code 39, Code 93, Code 128, ITF, UPC-A, UPC-E, Codabar
2D
PDF 417, QR code, DATA MATRIX

FONTS / GRAPHICS

Character Type
Font A(12x24), Font B(9x17), Chinese(Traditional/Simplified, 24x24), Korean(24x24), Japanese(24x24)
Characters per line (CPL)
Font A(12x24) : 42cpl,
Font B(9x17) : 56cpl,
Character set
95 Alphanumeric,
14 International,
128 x 18 Graphic

ACCESSORIES

Standard
Power Adaptor 24Vdc / 1.75A
Option
Melody Box

sewoo

Republic of Korea [Head Office / R&D Center]
28-6, Gajangsaneopdong-ro, Osan-si, Gyeonggi- do, 18103, Republic of Korea
T. +82-31-8077-5000 **F.** +82-31-624-5310 **E.** sales@miniprinter.com

www.miniprinter.com

USA, Inc.
Torrance, CA 90502, USA
T. +1-310-617-7401
E. NA_sales@miniprinter.com

México Office
Cuauhtémoc, D.F. Mexico. CP 06500
T. +52-1-55-3232-9543 **M.** +52-1-55-143893
E. LA_sales@miniprinter.com

China Office
Shang hai shi, Song jiang qu
T. +86-177-1729-9100
E. sales@miniprinter.com