sewoo

DIRECT THERMAL POS PRINTER

SLK-T21EBII



- Energy star qualified for power efficiency
- High speed printing : 220mm/sec
- Paper width adjustable 50~82.5mm
- ESC/POS command compatible
- Printing notice accessory : Melody box
- Wall mount installation availadle

Barcode

Durable

50~82.5MM

Paper width

Paper Sensor

Easy Loading

220 mm/sec

Fast Speed

Compact Design

Easy Maintenance

Energy Star

APPLICATION



SPECIFICATIONS

PRINTER CHARACTERISTICS

Print Method
Direct thermal
Print Speed
Up to 8.6ips(220mm/sec)
Print Width
Up to 2.8"(72mm)
Resolution
180dpi
Power
Power type : External SMPS
AC : 100~240Vac 50/60Hz
DC : 24Vdc / 1.75A
Sensor
Standard: Paper End, Paper Low, Cover Open
Option : Black Mark
Reliability
TPH life : 160km
MCBF : 60 Million lines
Cutter life : 1.8 Million cuts
Drawer port
2 circuits(24V, 1A Max.)

PHYSICAL CHARACTERISTICS

Dimension (W x D x H)
5.98" x 8.03" x 5.90"
(152 x 204 x 150mm)
Weight
3.74lb(1.7Kg)

INTERFACES

Standard
USB(B type)+
Serial(RS-232C_9pin)+
Ethernet Built-in

CERTIFICATIONS

CE, FCC, KC, UL/cUL,
ENERGY STAR

OPERATING CHARACTERISTICS

Operating Temperature
32 ~ 113°F(0 ~ 45°C)
Operating Humidity
10 ~ 80RH%
Storage Temperature
-4 ~ 140°F(-20 ~ 60°C)
Storage Humidity
10 ~ 90%

MEDIA CHARACTERISTICS

Media Type
Thermal recipt paper
Linerless(Optional)
Media Width
1.9~3.2"(50mm ~82.5mm)
Media Core Diameter
0.4"(12.5mm ± 0.5mm)
Media Roll Diameter
3.1"(ø 80mm)
Thickness
0.06~0.09mm

SOFTWARE

Emulations
ESC/POS Command compatible
Drivers
Windows Driver(XP ~, Server2003 ~), Windows CE & Mobile Driver (CE 4.2 ~, Mobile 5.0 ~), Linux Driver, Mac Driver, OPOS Driver, JavaPOS Driver, iOS SDK, Android(6.0 ~) SDK, Windows SDK, Windows CE SDK, Linux SDK

BARCODES

1D
EAN-8, EAN-13, Code 39, Code 93, Code 128, ITF, UPC-A, UPC-E, Codabar
2D
PDF 417, QR code, DATA MATRIX

FONTS / GRAPHICS

Character Type
Font A(12x24), Font B(9x17), Chinese(Traditional/Simplified, 24x24), Korean(24x24), Japanese(24x24)
Characters per line (CPL)
Font A(12x24) : 42cpl,
Font B(9x17) : 56cpl,
Character set
95 Alphanumeric,
14 International,
128 x 18 Graphic

ACCESSORIES

Standard
Power Adaptor 24Vdc / 1.75A
Option
Melody Box

sewoo

Republic of Korea [Head Office / R&D Center]
28-6, Gajangsaneopdong-ro, Osan-si, Gyeonggi- do, 18103, Republic of Korea
T. +82-31-8077-5000 **F.** +82-31-624-5310 **E.** sales@miniprinter.com

www.miniprinter.com

USA, Inc.
Torrance, CA 90502, USA
T. +1-310-617-7401
E. NA_sales@miniprinter.com

México Office
Cuauhtémoc, D.F. Mexico. CP 06500
T. +52-1-55-3232-9543 **M.** +52-1-55-143893
E. LA_sales@miniprinter.com

China Office
Shang hai shi, Song jiang qu
T. +86-177-1729-9100
E. sales@miniprinter.com