sewoo

Compact size and Enhanced usability

SLK-TS400



- Structure for easy maintenance
- Design for enhanced usability
- Compact footprint to help easily fit on the counter.
- Ideal for front exit printing with Wall mount.
- Supports flexible printing exit way Front exit or top exit.
- Ideal for kitchen/bar printer with melody box(Kitchen buzzer)
- Easy handling the jam of the paper with same cover opening/closing direction as paper cutting direction.

Rugged Design

Drop Resistant

Barcode

Durable

80mm
Paper Width

Easy Loading

220 mm/sec
High Speed

Compact Design

Easy Maintenance

Various interface

APPLICATION



SPECIFICATIONS

PRINTER CHARACTERISTICS

Print Method
Direct thermal
Print Speed
Up to 8.6ips(220mm/sec)
Print Width
Up to 2.8" (72mm)
Resolution
180 dpi
Power
Power type : External SMPS
AC : 100~240Vac 50/60Hz
DC : 24Vdc / 1.75A
Sensor
Paper end, Cover open
Reliability
TPH life : 160km
MCBF : 60 Million lines
Cutter life : 1.5 Million cuts
Drawer port
2 circuits(24V, 1A Max.)

PHYSICAL CHARACTERISTICS

Dimension (W x D x H)
5.1"×5.5"×6.0"
(130×140×154mm)
Weight
2.7lb(1.25Kg)

INTERFACES

Standard
USB(B type)+Serial
(RS-232C_25pin)Built-in,
USB(B type)+Ethernet Built-in
Optional
Wi-Fi(802.11a/b/g/n),
Bluetooth Ver 4.2(Bluegiga,iOS)

CERTIFICATIONS

CE, FCC, KC, UL/cUL, CB,
ENERGY STAR, TELEC

OPERATING CHARACTERISTICS

Operating Temperature
32 ~ 113°F(0 ~ 45°C)
Operating Humidity
35 ~ 80%
Storage Temperature
-4 ~ 140°F(-20 ~ 60°C)
Storage Humidity
10 ~ 90%

MEDIA CHARACTERISTICS

Media Type
Thermal recipt paper
Media Width
3.14"(80mm)
Media Core Diameter
0.4"(12.5mm)
Media Roll Diameter
3.1"(ø 83mm)
Thickness
0.06~0.09mm

SOFTWARE

Emulations
ESC/POS
Drivers
Windows Driver(XP ~, Server2003 ~),
Windows CE & Mobile Driver (CE 4.2 ~,
Mobile 5.0 ~), Linux Driver, Mac Driver,
OPOS Driver, JavaPOS Driver, iOS SDK,
Android(6.0 ~) SDK, Windows SDK,
Windows CE SDK, Linux SDK

BARCODES

1D
EAN-8, EAN-13, Code 39, Code 93,
Code 128, ITF, UPC-A, UPC-E,Codabar
2D
PDF 417, QR code, DATA MATRIX

FONTS / GRAPHICS

Character Type
Font A(12x24), Font B(9x17),
Chinese(Traditional/Simplified, 24x24),
Korean(24x24), Japanese(24x24)
Characters per line (CPL)
Font A(12x24) : 42cpl,
Font B(9x17) : 56cpl,
Character set
95 Alphanumeric,
14 International,
128 x 18 Graphic

ACCESSORIES

Standard
Power Adaptor 24Vdc / 1.75A
Option
Melody Box

sewoo

Republic of Korea [Head Office / R&D Center]
28-6, Gajangsaneopdong-ro, Osan-si, Gyeonggi- do, 18103, Republic of Korea
T. +82-31-8077-5000 **F.** +82-31-624-5310 **E.** sales@miniprinter.com

www.miniprinter.com

USA, Inc.
Torrance, CA 90502, USA
T. +1-310-617-7401
E. NA_sales@miniprinter.com

México Office
Cuauhtémoc, D.F. Mexico. CP 06500
T. +52-1-55-3232-9543 **M.** +52-1-55-143893
E. LA_sales@miniprinter.com

China Office
Shang hai shi, Song jiang qu
T. +86-177-1729-9100
E. sales@miniprinter.com