Specifications

Performance	Model	UROVO RT40S
	O S.	Android 13, GMS/AER
	Processor	Qualcomm Octa-core 2.45 GHz
	Memory	4GB RAM , 64GB ROM
	Extended memory	Micro SD card, Up to 256 GB
Basic specification	Dimension	199 x 58 x 29(thinnest) mm (7.834 x 2.283 x 1.14 inch)
	Weight	425g
	Display	4 inch 480*800 pixel
	Cover glass	Corning Gorilla Glass
	Main battery	3.85V 5,200mAh Support Hot Swap
	Charging time	Less than 3 hours
	Audio	Receiver, speaker, microphone Support PTT (Push-to-Talk), speaker loudness over 110dB at 10cm
	Buttons	Front Numeric (29 key), Function Numeric (38 key), Alpha Numeric (51 key) Vol+/- button, Scan button*2, Custom button*1
	Camera	Rear camera: 13M pixel with flashlight
	Sensors	Light + Accelerator+ Proximity + Geomagnetic+Gyro
	Scanning	Standard range scanner and extended range scanner are optional Support all industry-leading 1D/2D barcode on paper or screen
	Slots	Nano-SIM*1，PSAM/ SIM*1 (self-adaption)
Communication	WWAN	2G/3G/4G
	Bluetooth	BT 5.0 + BR/EDR + BLE
	Wi-Fi	IEEE 802.11 a/b/g/n/ac/d/h/i/k/r/v/w/mc/ax, 2.4GHz/ 5GHz Wi-Fi 6(802.11ax); 2 x 2 MU-MIMO
	GNSS	GPS, BeiDou, GLONASS, Galileo
Environment	Working temperature	Cold chain version: -30° C ~ +50° C (Equipped with heater of screen & imager window) Regular version: -20° C ~ +50° C
	Storage temperature	-40° C ~ +70° C
	Humidity	5% ~ 95% RH (non-condensing)
	Drop Specification	1.8m (5.9 ft.) flat concrete
	Tumble Specification	1000 times 1m (3.3 ft.)
	Sealing	IP68